

SRS Bitaktol KS



Low Smoke Two-Stroke Engine Oil

November 2012

Characteristics

SRS Bitaktol KS is a low smoke two-stroke engine oil.

Modern base oils using synthetic technology and special additives guarantee optimal lubrication and a high degree of engine cleanliness. Deposits in the combustion chamber and the exhaust system are prevented, smoke development is clearly reduced.

Application

SRS Bitaktol KS is self-mixing and can be used in blend ratios up to 1:50 and for separate lubrication (autolube systems).

SRS Bitaktol KS two-stroke engine oil meets the highest specifications for the Asian and European markets.

Performance / Specifications

- ISO L-EGD
- JASO FC
- API TC
- TISI
- Husqvarna Chainsaw

SRS Bitaktol KS is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Bitaktol KS
Density at 15°C	g/cm ³	DIN 51 757	0.872
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	67.5
Kin. Viscosity at 100°C	mm ² /s	DIN EN ISO 3104	9.53
Viscosity Index (VI)		DIN ISO 2909	121
Flash Point PM	°C	DIN EN ISO 2719	123
Pour Point	°C	DIN ISO 3016	-33
Base Number	mgKOH/g	DIN ISO 3771	1.1

The above values may vary within the commercial limits.

Made in Germany