

SRS Calibration Fluid CV



Calibration fluid for diesel injectors

November 2014

Characteristics

SRS Calibration Fluid CV is a low viscosity test-oil for the calibration of diesel injection pumps with a very close viscosity tolerance. It is noted for its excellent wear-, corrosion-protection and low foaming tendency.

Performance / Specifications

SRS Calibration Fluid CV meets the ISO standard 4113-CV-AW. SRS Calibration fluid CV is recommended by Bosch (VS 15665-OL-CV), MTU, MAN and Volkswagen. Further it is approved by MTU as a corrosion preventive oil for internal preservation of fuel systems.

Approvals / Recommendations

- ISO-standard 4113-CV-AW
- Bosch-standard VS 15665-OL-CV
- Bosch-Approval
- MTU-Approval as a corrosion protection oil for inside preservation or conservation of fuel systems
- MAN-Approval

SRS Calibration Fluid CV is a product of the H&R ChemPharm GmbH.

Typical data	Test method	SRS Calibration Fluid CV
Colour	DIN ISO 2049	<0,5
Density at 15°C	DIN 51 757	0.824
Viscosity at 20°C	DIN EN ISO 3104	3.85
Viscosity at 40°C	DIN EN ISO 3104	2.52
Flash point PM	DIN EN ISO 2719	115
Cloud point	ASTM D 2500	- 28
Initial Boiling Point	DIN 51 751	232
Final Boiling Point	DIN 51 751	265
Steel Corrosion Test	DIN ISO 7120	0 – A
Copper Corrosion Test	DIN ISO 2160	1
Corrosion Protection:		
Humidity Cabinet Test	ASTM D 1748	6 x 0

The above values may vary within the commercial limits.

Made in Germany