

SRS Calibration Fluid



Calibration Fluid

March 2013

Characteristics

SRS Calibration Fluid is a test oil for the calibration of diesel injection pumps. It is characterized by its high antiwear capability, corrosion protection and low foaming tendency.

Performance / Specifications

SRS Calibration Fluid meets ISO standard 4113.

Furthermore it is approved by MTU as a corrosion protection oil for inside preservation or conservation of fuel systems.

Approvals / Recommendations

- Bosch Norm VS 15665-OL
- ISO standard 4113
- MTU Approval as a corrosion protection oil for inside preservation or conservation of fuel systems

SRS Calibration fluid is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Calibration Fluid
Density at 15°C	g/cm ³	DIN 51 757	0.824
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	2.48
Flash Point PM	°C	DIN EN ISO 2719	105
Cloud Point	°C	ASTM D 2500	- 28
Initial Boiling Point	°C	DIN 51 751	232
Final Boiling Point	°C	DIN 51 751	265
Steel Corrosion Test	Grade	DIN 51 585	0 – A
Copper Corrosion Test	Grade	DIN ISO 2160	1
Corrosion Protection:			
Humidity Cabinet Test	Grade	DIN 51 359	6 x 0

The above values may vary within the commercial limits.

Made in Germany