

SRS Cargolub TFG plus



High Performance Low Friction Engine Oil

May 2016

Characteristics

SRS Cargolub TFG plus is a highly additivated UHPD low friction engine oil for commercial vehicles. Engine manufacturers prefer SAE 10W-40 as year-round grade which is achieved through the use of selected base oils. At low temperature SAE 10W assures excellent cold starting (low cold start wear) and quickest possible oil supply of all engine lubricating points. Extreme conditions are safely controlled by SAE 40 high-temperature viscosity. Friction losses and wear are reduced. The economy is improved through low oil and fuel consumption as well as through higher engine reliability.

Application

SRS Cargolub TFG plus is especially designed for economic supply of exhaust-optimized engines, even under extreme conditions. SRS Cargolub TFG plus assures excellent oxidation and rust protection and stability at high temperatures through the use of special additive systems. High dispersion capacity and piston cleanliness prevent deposits in the engine compartment which may eventually cause a power drop.

SRS Cargolub TFG plus is a year-round high-performance engine oil for use in commercial vehicles, adapted to the EU exhaust standards. It is also in full compliance with all standards for older naturally aspirated and stationary diesel engines.

Performance / Specifications

- SAE Grade 10W-40
- ACEA E4 / E7
- API CI-4

Approvals / Recommendations

- | | |
|------------------------------|---------------------------|
| • MAN M 3277 | • MTU MTL 5044 Type 3 |
| • Scania LDF-2 | • MTU DDC BR 2000/4000 |
| • Volvo VDS-3 (STD 417-0002) | • DAF |
| • Deutz DQC III-10 | • Mack EO-N / EO-M Plus |
| • Renault VI RLD-2/RXD | • Cummins CES 20077/20078 |
| • MB 228.5 | • Detroit Diesel 93K215 |

SRS Cargolub TFG plus is a product of the H&R ChemPharm GmbH.

| Typical Data | Test Method | SRS Cargolub TFG plus |
|-------------------------------|-----------------|-----------------------|
| SAE Grade | SAE J 300 | 10W-40 |
| Density at 15°C | DIN 51 757 | 0.871 |
| Dyn. Viscosity at -25°C (CCS) | DIN 51 757 | 5,690 |
| Kin. Viscosity at 40°C | DIN EN ISO 3104 | 92.1 |
| Kin. Viscosity at 100°C | DIN EN ISO 3104 | 14.0 |
| Viscosity Index (VI) | DIN ISO 2909 | 156 |
| Flash Point COC | DIN ISO 2592 | 232 |
| Pour Point | DIN ISO 3016 | -39 |
| Total Base Number | DIN ISO 3771 | 13.2 |

The above values may vary within the commercial limits.

Made in Germany