

SRS Getriebefluid MGS plus 75W-90



Multipurpose Gear Oil

June 2017

Characteristics

SRS Getriebefluid MGS plus 75W-90 is a transmission oil for heavily loaded manual transmissions. Selected base oils using synthetic technology and innovative additives are balanced for the specific requirements of manual transmissions.

SRS Getriebefluid MGS plus 75W-90 provides excellent oxidation stability particularly high load capacity, optimal viscosity-temperature behaviour with very good low temperature fluidity and high shear stability. Excellent cold start behavior ensures optimum lubrication safety during the cold start phase. Extreme demands can be safely controlled under all temperatures and conditions.

Application

SRS Getriebefluid MGS plus 75W-90 is intended for high loaded manual transmissions (with and without synchronizing), transfer box gears and steering gears in vehicles and engines. It can be used as initial and service fills of manual transmissions and automatic transmissions in commercial vehicles according to ZF TE-ML 02B. In addition, the SRS Getriebefluid MGS plus 75W-90 can be used in transmissions and axles for lift trucks, where gear oils according to ZF TE-ML 17A are required.

Performance / Specifications

- SAE Grade 75W-90
- API GL-4

- MAN 341 Z2
- ZF TE-ML 02B, 17A

SRS Getriebefluid MGS plus 75W-90 is a product of H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Getriebefluid MGS plus 75W-90
SAE Grade	SAE J 306	75W-90
Density at 15°C	DIN 51 757	0.877
Dyn. Viscosity at -40°C	DIN 51 398	97,300
Kin. Viscosity at 40°C	DIN EN ISO 3104	78.7
Kin. Viscosity at 100°C	DIN EN ISO 3104	14.6
Viscosity Index (VI)	DIN ISO 2909	195
Flash Point COC	DIN ISO 2592	206
Pour Point	DIN ISO 3016	-42

The above values may vary within the commercial limits.

Made in Germany