

SRS ViVA 1 Longlife



High Performance Low Friction Engine Oil

September 2017

Characteristics

SRS ViVA 1 Longlife is a high performance low friction engine oil of viscosity grade SAE 5W-30. Base oils using synthetic technology and innovative additives matched to them ensure that the demands of today's practice are met. Excellent cold starting ensures optimal security of lubrication in the cold running phase. Extreme loads and high temperatures are safely handled under all operating conditions. SRS ViVA 1 Longlife contributes to the protection of the environment through its high fuel saving and the consequent reduction in emissions.

Application

SRS ViVA 1 Longlife is a top quality for passenger car gasoline and diesel engines of the new generation. The highest demands currently made on automobile engine oils are satisfied with more than enough reserve even after extended oil change intervals.

Performance / Specifications

- SAE Grade 5W-30
- ACEA A3/B4
- API SL

Approvals / Recommendations

- MB-Approval 229.5
- BMW Longlife-01
- VW-Norm 502 00 and 505 00
- Renault RN 0700
- Opel GM-LL-A 025
- Opel GM-LL-B 025

SRS ViVA 1 Longlife is a product of the H&R ChemPharm GmbH.

Typical data	Test method	SRS ViVA 1 Longlife
SAE Grade	SAE J 300	5W-30
Density at 15°C	DIN 51 757	0.854
Dyn. Viscosity at -30°C	ASTM D 5293	5,910
Kin. Viscosity at 40°C	DIN EN ISO 3104	69.1
Kin. Viscosity at 100°C	DIN EN ISO 3104	12.0
Viscosity Index (VI)	DIN ISO 2909	172
Flash point COC	DIN ISO 2592	237
Pour point	DIN ISO 3016	-41
Total base number	DIN ISO 3771	11.4

The above values may vary within the commercial limits.

Made in Germany