

SRS ViVA 1 SLV plus



High Performance Low Friction Engine Oil

June 2015

Characteristics

SRS ViVA 1 SLV plus is a high performance low friction engine oil for passenger cars of the newest technology.

Excellent low temperature flow characteristics protect optimal the engine during the cold starting. Extreme loads and high temperatures are safely handled under all operating conditions. SRS ViVA 1 SLV plus contributes through its high fuel economy and reduction of emissions to protect the environment.

Application

SRS ViVA 1 SLV plus has been especially developed for engines on Longlife service (WIV) of the Volkswagen group. It can be used in earlier models of VW. The service manual of the OEM must be followed. Oil change intervals up to 50.000 km or 2 years are possible.

SRS ViVA 1 SLV plus can also be used in gasoline and diesel engines of other passenger car manufacturers. This particular low emission engine oil keeps clean the emission reduction system of diesel engines during a long service time.

SRS ViVA 1 SLV plus can be used in gasoline and diesel engines which require motor oils according to ACEA A3/B4.

Performance / Specifications

- SAE Grade 5W-30
- ACEA C3
- API SN

Approvals / Recommendations

- VW Norm 504 00 and 507 00
- MB-Approval 229.51
- BMW Longlife-04
- Porsche C30

SRS ViVA 1 SLV plus is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS ViVA 1 SLV plus
SAE Grade	SAE J 300	5W-30
Density at 15°C	DIN 51 757	0.853
Dyn. Viscosity at -30°C (CCS)	ASTM D 5293	5,910
Kin. Viscosity at 40°C	DIN EN ISO 3104	66.5
Kin. Viscosity at 100°C	DIN EN ISO 3104	11.6
Viscosity Index (VI)	DIN ISO 2909	171
Flash Point COC	DIN ISO 2592	240
Pour Point	DIN ISO 3016	-45
Total Base Number	DIN ISO 3771	6.2

The above values may vary within the commercial limits.

Made in Germany