

# SRS ViVA 1 special V eco



Special High Performance Low Friction Engine Oil

May 2017

## Characteristics

**SRS ViVA 1 special V eco** is a high performance low friction 0W-20 engine oil based on modern synthetic technology.

Excellent low temperature flow characteristics protect optimal the engine during the cold starting. Extreme loads and high temperatures are safely handled under all operating conditions. It ensures extremely high wear protection and significantly reduced friction losses and is extremely shear-resistant.

SRS ViVA 1 special V eco contributes through its high fuel economy and reduction of emissions to protect the environment.

## Application

**SRS ViVA 1 special V eco** is a top quality for the latest Volvo VEA passenger car engines and is especially approved according to the Volvo specification VCC RBS0-2 AE.

## Performance / Specification

- SAE Grade 0W-20
- ACEA C5

## Approvals / Recommendations

- Volvo VCC RBS0-2AE

SRS ViVA 1 special V eco is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS ViVA 1 special V eco
SAE Grade	SAE J 300	0W-20
Density at 15°C	DIN 51 757	0.845
Dyn. Viscosity at -35°C (CCS)	ASTM D 5293	5,500
Kin. Viscosity at 40°C	DIN EN ISO 3104	44.0
Kin. Viscosity at 100°C	DIN EN ISO 3104	8.63
Viscosity Index (VI)	DIN ISO 2909	179
Flash Point COC	DIN ISO 2592	238
Pour Point	DIN ISO 3016	-48
Total Base Number	ASTM D 2896	7.9

The above values may vary within the commercial limits.

**Made in Germany**