

# SRS Violin Hypoid-Getriebeöl 85W-140



Gear Oil for Drive Axles

January 2016

## Characteristics

**SRS Violin Hypoid-Getriebeöl 85W-140** is blended from selected base oils with carefully adapted additives. Its viscosity is chosen to ensure both no channelling at low temperatures and high lubrication safety at high temperatures.

## Application

**SRS Violin Hypoid-Getriebeöl 85W-140** is intended for very high loaded hypoid meshed axles, bevel and spur gears, steering gears and not synchronized gear boxes in vehicles and machines.

## Performance / Specifications

- SAE Grade 85W-140
- API GL-5
- MIL-L-2105 C/D

## Approvals / Recommendations

- ZF Approval Number ZF000443  
ZF TE-ML 16D, 21A
- Volvo 97310
- DAF

SRS Violin Hypoid-Getriebeöl 85W-140 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Violin Hypoid Getriebeöl 85W-140
SAE Grade	SAE J 306	85W-140
Density at 15°C	DIN 51 757	0.906
Dyn. Viscosity at -26°C	DIN 51 398	-
Dyn. Viscosity at -12°C	DIN 51 398	89,000
Kin. Viscosity at 40°C	DIN EN ISO 3104	337
Kin. Viscosity at 100°C	DIN EN ISO 3104	24.7
Viscosity Index (VI)	DIN ISO 2909	95
Flash Point COC °C	DIN ISO 2592	220
Pour Point	DIN ISO 3016	-21
FZG-Test A/8.3/90	DIN ISO 14635	>12

The above values may vary within the commercial limits.

**Made in Germany**