

SRS Violin Mehrzweck-Getriebeöl 80W-90



Multipurpose Gear Oil for Manual Transmissions

January 2016

Characteristics

SRS Violin Mehrzweck-Getriebeöl 80W-90 multi-purpose gear oil is made of selected base oils with specially selected additives. Its viscosity is chosen to ensure no channelling at low temperatures and high lubrication safety at high temperatures.

Application

SRS Violin Mehrzweck-Getriebeöl 80W-90 is an EP multi-purpose gear oil which can be used for all gear boxes (with and without synchromesh), transfer gear boxes, various steering gears and normally loaded drive axles – particularly passenger car transaxle systems – insofar as hypoid gear oils in accordance with MIL-L-2105 B/C or API GL-5 are not stringently prescribed.

Performance / Specifications

- SAE Grade 80W-90
- API GL-4
- MIL-L-2105

Approvals / Recommendations

- ZF Approval Number ZF000440
ZF TE-ML 16A, 17A, 19A

SRS Violin Mehrzweck-Getriebeöl 80W-90 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Violin Mehrzweck-Getriebeöl 80W-90
SAE Grade	SAE J 306	80W-90
Density at 15°C	DIN 51 757	0.891
Dyn. Viscosity at -26°C	DIN 51 398	137,000
Dyn. Viscosity at -12°C	DIN 51 398	-
Kin. Viscosity at 40°C	DIN EN ISO 3104	141
Kin. Viscosity at 100°C	DIN EN ISO 3104	14
Viscosity Index (VI)	DIN ISO 2909	99
Flash Point COC °C	DIN ISO 2592	224
Pour Point	DIN ISO 3016	- 27
FZG-Test A/8.3/90	DIN ISO 14 635	> 12

The above values may vary within the commercial limits.

Made in Germany