

SRS Violin Mehrzweck-Getriebeöl 85W-140



Multipurpose Gear Oil for Manual Transmissions

January 2013

Characteristics

SRS Violin Mehrzweck-Getriebeöl 85W-140 multi-purpose gear oil is made of selected base oils with specially selected additives. Its viscosity is chosen to ensure no channelling at low temperatures and high lubrication safety at high temperatures.

Application

SRS Violin Mehrzweck-Getriebeöl 85W-140 is an EP multi-purpose gear oil which can be used for all gear boxes (with and without synchromesh), transfer gear boxes, various steering gears and normally loaded drive axles – particularly passenger car transaxle systems – insofar as hypoid gear oils in accordance with MIL-L-2105 B/C or API GL-5 are not stringently prescribed.

Performance / Specifications

- SAE Grade 85W-140
- API GL-4
- MIL-L-2105

SRS Violin Mehrzweck-Getriebeöl 85W-140 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Violin Mehrzwecke-Getriebeöl 85W-140
SAE Grade	SAE J 306	85W-140
Density at 15°C	DIN 51 757	0.902
Dyn. Viscosity at -26°C	DIN 51 398	-
Dyn. Viscosity at -12°C	DIN 51 398	118,000
Kin. Viscosity at 40°C	DIN EN ISO 3104	399
Kin. Viscosity at 100°C	DIN EN ISO 3104	26.6
Viscosity Index (VI)	DIN ISO 2909	90
Flash Point COC °C	DIN ISO 2592	285
Pour Point	DIN ISO 3016	- 18
FZG-Test A/8.3/90	DIN ISO 14 635	> 12

The above values may vary within the commercial limits.

Made in Germany