

SRS Bitaktol KX



Two-Stroke Engine Oil

November 2012

Characteristics

SRS Bitaktol KX is self-mixing mineral oil based high performance two-stroke engine oil. The requirements for piston cleanliness, corrosion protection, ring sticking, piston seizure and pre-ignition are clearly fulfilled.

SRS Bitaktol KX is recommended in accordance with manufacturer's recommendations for mixing ratios up to 1:50 and for separate lubrication (autolube systems).

Performance / Specifications

- ISO L-EGB
- JASO FB
- API TC

SRS Bitaktol KX is a product of the H&R ChemPharm GmbH.

| Typical Data | | Test Method | SRS Bitaktol KX |
|-------------------------|--------------------|-----------------|-----------------|
| Density at 15°C | g/cm ³ | DIN 51 757 | 0.878 |
| Kin. Viscosity at 40°C | mm ² /s | DIN EN ISO 3104 | 63.6 |
| Kin. Viscosity at 100°C | mm ² /s | DIN EN ISO 3104 | 8.6 |
| Viscosity Index (VI) | | DIN ISO 2909 | 108 |
| Flash Point PM | °C | DIN EN ISO 2719 | 141 |
| Pour Point | °C | DIN ISO 3016 | -24 |
| Base Number | mgKOH/g | DIN ISO 3771 | 1.25 |

The above values may vary within the commercial limits.

Made in Germany