

SRS Magnum 4T



4-Stroke Motorcycle Engine Oil

November 2011

Characteristics

SRS Magnum 4T is an engine oil specially developed for use in four-stroke motorcycle engines. It satisfies the technical demands of all motorcycle manufacturers, and is suitable for all air-cooled and water-cooled 4-stroke motorcycle engines. High engine cleanliness and wear protection increase the life of the engine. It is suitable for wet clutches. Grabbing and slipping clutches after a cold start are prevented.

Application

SRS Magnum 4T is a mineral oil based high performance engine oil in the SAE 20W-50 viscosity range. Very good high temperature stability and high wear protection guarantee optimal lubrication even under unfavourable conditions. The engine is protected from deposits and oil-sludge, oil consumption is reduced significantly.

Performance / Specifications

- SAE Grade 20W-50
- API SG
- JASO MA2

SRS Magnum 4T is product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Magnum 4T
SAE Grade	SAE J 300	20W-50
Density at 15°C	DIN 51 757	0.888
Kin. Viscosity at 40°C	DIN EN ISO 3104	150
Kin. Viscosity at 100°C	DIN EN ISO 3104	16.7
Viscosity Index (VI)	DIN ISO 2909	119
Flash Point COC	DIN ISO 2592	235
Pour Point	DIN ISO 3016	-30

The above values may vary within the commercial limits.

Made in Germany