

SRS Magnum 4T plus



High Performance 4-Stroke Motorcycle Engine Oil

April 2013

Characteristics

SRS Magnum 4T plus is an engine oil specially developed for use in four-stroke motorcycle engines. It satisfies the technical demands of all motorcycle manufacturers, and is suitable for all air-cooled and water-cooled 4-stroke motorcycle engines. High engine cleanliness and wear protection increase the life of the engine. It is suitable for wet clutches. Grabbing and slipping clutches after a cold start are prevented.

Application

SRS Magnum 4T plus is a SAE 10W-40 high performance engine oil based on synthetic technology. Optimal lubrication at high temperatures and high engine revolutions guarantee best engine protection even under the most extreme conditions. Deposits on pistons and valves are reliably prevented, exceptional engine cleanliness is promoted. The low viscosity at low temperatures helps the oil to penetrate quickly the engine, to start without cold start wear.

Performance / Specifications

- SAE Grade 10W-40
- ACEA A3
- API SL
- JASO MA2

SRS Magnum 4T plus is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Magnum 4T plus
SAE Grade	SAE J 300	10W-40
Density at 15°C	DIN 51 757	0.873
Kin. Viscosity at 40°C	DIN EN ISO 3104	95
Kin. Viscosity at 100°C	DIN EN ISO 3104	14.2
Viscosity Index (VI)	DIN ISO 2909	155
Flash Point COC	DIN ISO 2592	225
Pour Point	DIN ISO 3016	-33

The above values may vary within the commercial limits.

Made in Germany