

SRS Bitaktol KS plus



Fully Synthetic High Performance Two-Stroke Engine Oil

February 2026

Characteristics

SRS Bitaktol KS plus is a fully synthetic high performance self-mixing two-stroke engine oil. The requirements for piston cleanliness, corrosion protection, ring sticking, piston seizure and pre-ignition are fulfilled by far using synthetic components.

Application

SRS Bitaktol KS plus is a low ash engine oil for heavy-duty two-stroke engines (low-smoke). Mixing ratios up to 1:100 according to manufacturer's recommendations are possible.

Specifications

- ISO L-EGD
- JASO FD
- API TC
- TISI

Recommendations

- Husqvarna Chainsaw
- Piaggio
- Rotax Snowmobile

SRS Bitaktol KS plus is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Bitaktol KS plus
Density at 15°C	g/cm ³	DIN EN 12185	0.897
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	53.7
Kin. Viscosity at 100°C	mm ² /s	DIN EN ISO 3104	9.0
Viscosity Index (VI)		DIN ISO 2909	148
Flash Point PM	°C	DIN EN ISO 2719	112
Pour Point	°C	ASTM D 5950	< -42

The above values may vary within the commercial limits.

Made in Germany