

SRS Violin ATF CVT



ATF for Continuously Variable Transmission (CVT)

May 2025

Characteristics

SRS Violin ATF CVT is a transmission oil for continuously variable transmission made from selected base oils and a high performance additive package based on modern synthetic technology. SRS Violin ATF CVT is suitable for use in continuous variable transmissions with steel-steel thrust belts or chains. It offers very good wear, corrosion and oxidation protection for reliable operation and longest life and a high friction stability

Application

SRS Violin ATF CVT is suitable for use in most passenger cars fitted with push belt transmissions.

SRS Violin ATF CVT is not suitable for use in hybrid CVT's (Honda/Ford), DCT (Dual Clutch Transmission) or automatic stages.

Recommendations

(Further recommendations on request)

- Audi Multitronic
- BMW Mini Cooper EZL799A
- Chery CVT, WCF-1
- Citroen PSA Standard 9735 EF
- Daihatsu Ammix CVT DFE
- Daihatsu Ammix CVT Fluid DC, DFC
- Dodge / Jeep / Chrysler NS-2
- Dodge / Chrysler / Jeep Mopar CVT+4
- Fiat Tutela Car CVT N.G.
- Ford WSD-M2C-199A
- GM / Saturn DEX-CVT, CVT I-Green2
- GM VT40 / GM HP CVT
- Honda HMMF Ultra (without starting clutch)
- Honda HCF2
- Honda Z-1 (CVT without starting clutch)
- Honda Ultra HEVF-Type 1
- Hyundai / KIA CVT-1, SP III (CVT model)
- Idemitsu CVTS-EX1
- Lexus Fluid TC, Fluid FE
- Mazda JWS 3320
- MG Rover EM-CVT
- Mini Cooper EZL 799 / EZL799A / ZF CVT V1
- Mitsubishi CVT Fluid -MA1; CVTF-J1, J4 and J4+
- Mitsubishi CVTF ECO J4
- Mitsubishi (Diaqueen) SP-III (CVT model only)
- Nissan NS-1, NS-2, NS-2V, NS-3, N-CVT
- Opel/Vauxhall 7-speed CVT
- Peugeot PSA Standard 9735 EF
- Punch CVTF-EX1 for Punch VT2 / VT3 Transmissions
- Subaru iCVT, iCVT FG, ECVT
- Subaru Lineartronic chain CVT, CVT II and CVT 3 Fluid
- Subaru ECVT
- Subaru Lineartronic High Torque (HT) CVT Fluid, CV 30
- Suzuki CVTF TC, CVTF 3320, CVTF 4401, NS-2, CVT Green 1&2, CVT Green 1V
- Toyota CVTF TC, CVTF FE
- Volvo CVT 4959
- VW / Audi TL 521 16 (G 052 516)
- VW / Audi TL 521 80 (G 052 180)
- e-Mobility:
- Ford Escape Hybrid with eCVT
- Honda e:HEV, iMMD
- Jatco JR712E, CVT 8 Hybrid
- Mazda SKYACTIVE-HYBRID
- Nissan e Power, Altima Hybrid
- Toyota THSII / Toyota Prius, THS 5th Gen. / Toyota Noah, Voxy etc.

SRS Violin ATF CVT is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Violin ATF CVT
Colour			Red
Density at 15°C	g/cm ³	DIN 51 757	0.848
Dyn. Viscosity at - 40°C	mPa s	ASTM D 2983	8,500
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	32.6
Kin. Viscosity at 100°C	mm ² /s	DIN EN ISO 3104	6.99
Viscosity Index (VI)		DIN ISO 2909	183
Flash Point COC	°C	DIN ISO 2592	212
Pour Point	°C	DIN ISO 3016	- 48

The above values may vary within the commercial limits.

Made in Germany